

# FLIGHT-ENGINEERED MICROPHONES

BY *Electro-Voice*<sup>®</sup>

**MODEL 205STCKKP Differential Carbon** — Close-talking, noise-cancelling, single button carbon. For aircraft and emergency communications. FAA approved — Certificate No. 1040. Blastproof, waterproof and shock resistant. Output at ¼": —50 db. Lo-Z. Black phenolic case. Press-to-talk switch closes microphone and relay circuit. Mounting bracket furnished. Coiled cord extends to 5'. Size: 2¼" w. x 4" h. x 2" d. Net weight 12 oz. List Each .....\$54.75

**MODEL 603TR TRANSISTORIZED NOISE CANCELING MOBILE** — Developed especially for aircraft applications, the 603TR is a superior, highly reliable microphone providing all dynamic advantages for direct replacement of carbon units. Rejects sounds originating more than ¼" away for elimination of high ambient background noise. Built-in transistor amplifier with 48 db. gain matches output level of carbon circuits. Output adjustable with internal potentiometer up to —16 db. Magnetic hanger bracket furnished, holds face of microphone. Acoustalloy<sup>®</sup> diaphragm. Response: 200-4,000 Hz. Coiled cord extends to 5'. Press-to-talk switch shorts microphone in "off" position and provides relay control. Lo-Z. Size: 2¼" w. x 3½" h. x 1¾" d. Net weight, 8 oz. List Each .....\$140.00

**MODEL 602TR** — Similar to 603TR with different case design, uses conventional hanger which is supplied. Fixed output level. —23 db. Response: 100-5,000 Hz. Size: 2¾" w. x 4" h. x 2" d. Net weight, 13 oz. List Each .....\$93.00

**MODEL 625SKK DYNAMIC DIFFERENTIAL HANDSET** — For paging, intercom, and communications. Sturdy phenolic case contains noise-canceling Lo-Z microphone and 150 ohm magnetic receiver. Response: 100-5,000 Hz. Output: —55 db. Grip-to-talk switch closes microphone and relay circuit. Five-conductor coiled cord extends to 5'. Size: 2¾" w. x 8½" l. x 3" d. Net weight, 1 lb. 8 oz. List Each .....\$85.00

**MODEL 606 DIFFERENTIAL DYNAMIC**—Close talking, noise cancelling. Accepts sounds of close origin (¼") and rejects sounds of distant origin. Response: 100 to 5,000 Hz. Output at ¼": —55 db. Acoustalloy<sup>®</sup> diaphragm. ⅝"-27 thread. Built-in connector. Satin Chrome finish. Size: 3¼" h. including stud x 2" dia. Hi-Z or balanced Lo-Z, must be specified. 15' cable. Net weight, 8 oz. less cable. List Each .....\$52.50

**MODEL 428 TOUCH-TO-TALK STAND**—Fits standard ⅝"-27 thread. Lever-type DPDT switch for relay operation or microphone On-Off—closes or opens instantly or locks in "talk" position. Satin chrome; gray plastic switch lever with locking button. 7" x 5½" base diameter. Net Weight, 1¾ lbs. List Each .....\$30.00

