



NOTES:

- 1) INSTALL J1 & J3 FOR NORMALLY UNMUTED OPERATION. IN THIS MODE A CONTACT CLOSURE SUPPLIED ACROSS THE MUTE, TERMINALS (AVAILABLE AT THE REAR OF THE AMPLIFIER) WILL MUTE THE OUTPUT.
- 2) REMOVE J1 & J3, AND INSTALL J2 FOR NORMALLY MUTED OPERATION. IN THIS MODE, THE OUTPUT IS NORMALLY MUTED AND WILL UNMUTE BY SUPPLYING A CONTACT CLOSURE AT THE MUTE 1 TERMINAL AVAILABLE AT THE REAR OF THE AMPLIFIER.
- 3) INSTALL J1 & J4 FOR NORMALLY UNMUTED OPERATION IN THIS MODE. A CONTACT CLOSURE SUPPLIED ACROSS THE MUTE 2 TERMINALS (AVAILABLE AT THE REAR OF THE AMPLIFIER) WILL MUTE THE OUTPUT.

DATE 3-89	TITLE	UNIVERSITY SOUND INC	
DRWN KLK	ELECTRICAL SCHEMATIC CRL-12	SIZE	DRAWING #
ENGR KLK		B	600-9506-00
APRVD		SHEET	1 OF 1
REV	FCN #	DATE	TOLERANCE

UNIVERSITY SOUND INC	DATE 3-89	TITLE	LINE MODULE
600-9506-00	DRWN KLK	ENGR KLK	CRL-12
APRVD	APRVD	REV	03
REV	FCN #	DATE	TOLERANCE