



**University  
Sound, Inc.**  
a MARK IV company

# UPI-10/UPI-10T

## PERMANENT INSTALLATION SPEAKER SYSTEM

### SPECIFICATIONS

**Frequency Response:**

96-18,000 Hz  $\pm 5$  dB (see Figure 3)

**Usable Low-Frequency Limit**

(10-dB-down point):

76 Hz

**Power Handling:**

8 hours, 6 dB crest factor, 15 watts (per  
ANSI/EIA RS-426-A 1980)

30 watts program

**Impedance,**

Nominal: 8.0 ohms

Minimum: 7.0 ohms

**Sound Pressure Level at 1 Meter,  
1 Watt Input, Anechoic Environment,  
Band-Limited Pink-Noise Signal,**

500 to 5,000 Hz:

90 dB

**Horizontal Beamwidth:**

160° @ 2 kHz (see Figure 2)

**Vertical Beamwidth:**

180° @ 2 kHz (see Figure 2)

**Directivity Factor  $R_0(Q)$**

3.1 @ 2 kHz

**Transducer Complement,**

10.1-cm (4-inch) full-range loudspeaker

**Box Tuning Frequency:**

80 Hz

**Enclosure Materials:**

High-density particle board covered  
with black, wood-simulation vinyl.

A heavy-duty, black, powder-coated  
grille is provided.

**Optional Accessories:**

UPI-10MB mounting bracket

**Dimensions:**

27.9 cm (11.0 in.) high,

20.3 cm (8.0 in.) wide,


20.3 cm (8.0 in.) deep

**Net Weight (Each):**

3.2 kg (7 lb)

**Shipping Weight (Pair):**

7.7 kg (17 lb)



### DESCRIPTION

The University Sound UPI-10 is a full-range loudspeaker system intended for the reproduction of speech or music. It is ideally suited for indoor applications where a distributed ceiling-speaker system cannot be installed. Its compact size and wide dispersion make the UPI-10 the choice of professional users as a background loudspeaker in restaurants and clubs. Threaded inserts in the cabinet, in combination with either the OmniMount® Series 25 or the UPI-10MB mounting bracket, provide a flexible mounting system for virtually any application.<sup>1</sup>

The system is fitted with a 4-inch, full-range, direct-radiating woofer installed in an optimally vented enclosure. This combination produces an extended bass response with high efficiency for a relatively small enclosure. The enclosure is finished in an attractive black wood-simulation vinyl and is provided with a black metal grille. The UPI-10T is provided with a 25/70-volt line transformer with switch settings of 1, 2, 4 and 8 watts.




### ARCHITECTS AND ENGINEERS SPECIFICATIONS

The loudspeaker shall be a full-range system utilizing a 10-cm (4-inch) loudspeaker. The loudspeaker system shall meet the following performance criteria: Power handling: 15 watts per ANSI/EIA RS-426-A 1980. Frequency response:  $\pm 5$  dB from 96 Hz to 18 kHz. Pressure sensitivity: 90 dB SPL at one watt, 500 Hz to 5 kHz measured at a distance of one meter on axis. Impedance: 8 ohms nominal, 7.0 ohms minimum.

The enclosure shall be constructed of high-density particle board and covered with a black wood-simulation vinyl. A black metal grille will be provided. The unit shall be 27.9 cm (11.0 inch) high, 20.3 cm (8.0 inch) wide, 20.3 cm (8.0 inch) deep. The loudspeaker system shall be the University Sound model UPI-10.

When provided with an optional 25/70-volt line transformer, tapped at 1, 2, 4 and 8 watts, the loudspeaker shall be the University Sound model UPI-10T

1. OmniMount® is a registered trademark of OmniMount Systems.



#### **POLAR RESPONSE**

The directional characteristics of the UPI-10 were measured by running a set of horizontal/vertical polar responses, in University's large anechoic chamber, at each one-third-octave center frequency. The test signal was one-third-octave, pseudo-random pink noise centered at the indicated frequencies. The measurement microphone was placed 6.1 m (20 ft) from the horn mouth, while rotation was about the wave guide geometric apexes. These axes of rotation are quite close to the apparent (acoustic) apexes across the frequency range of measurement. Errors attributable to the slight differences between the geometric and acoustic apexes are reduced to an inconsequential level by the relatively long, 20-foot measuring distance. The polar plots shown in Figure 1 display the results of these tests. The center frequency is noted on each plot.

#### **BEAMWIDTH**

A plot of the UPI-10 6-dB-down total included beamwidth angle is shown in Figure 2 for each one-third-octave center frequency.

#### **FREQUENCY RESPONSE**

Figure 3 shows the axial frequency response of the UPI-10. It was measured at a distance of 1 meter, using a swept sine wave.

**WARRANTY (Limited)** — University Sound Speakers and Speaker Systems (excluding active electronics) are guaranteed for five years from date of original purchase against malfunction due to defects in workmanship and materials. If such malfunction occurs, unit will be repaired or replaced (at our option) without charge for materials or labor if delivered prepaid to University Sound. Unit will be returned prepaid. Warranty does not extend to finish, appearance items, burned coils, or malfunction due to abuse or operation under other than specified conditions, including cone and/or coil damage resulting from improperly designed enclosures, nor does it extend to incidental or consequential damages. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above exclusion may not apply to you. Repair by other than University Sound will void this guarantee. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

**For warranty repair and service information on University Sound products,** contact: University Sound, Inc., 13278 Ralston Avenue, Sylmar, CA 91342-7607; Phone: 818-362-9516; FAX: 818-362-3463; Attention: Customer Service Department.

**For technical assistance,** contact the Technical Services Representative at University Sound, Inc.

#### **Repair locations:**

Speaker products including LR Line radiators, PI Series speakers, CDP848AT, CDP850T, Musicastor100, FC100, Interface Series, MC Series, SP Series, and TK60: University Sound, Inc., 600 Cecil Street, Buchanan, MI 49107; Attention: Service Department

All other paging speakers and speaker products: University Sound, Inc., 10500 West Reno, Oklahoma City, OK 73125; Attention: Service Department.

Specifications subject to change without notice.

## BASIC GUIDELINES FOR THE USE OF HORNS AND DRIVERS WITHIN A SOUND SYSTEM.

### DESIGNING FOR INTELLIGIBILITY AND ADEQUATE SPL

#### The Basic Idea

Many sound systems would have better performance if the following basic principles are kept in mind. Speakers with the appropriate coverage patterns should be chosen, aimed and powered to achieve a uniform direct field in the highly absorptive audience, with no sound aimed at the reflective wall and ceiling surfaces. Where multiple speakers are required in order to achieve a uniform direct field, their coverage patterns should be only slightly overlapped, so that each section of the audience is covered by a single speaker. To the extent this ideal is achieved, reverberation is minimized and intelligibility is maximized.

The following material explains these concepts in more detail and illustrates two design approaches.

#### What is Reverberation?

Reverberation is the persistence of sound within an enclosure, such as a room, after the original sound has ceased. Reverberation may also be considered as a series of multiple echoes so closely spaced in time that they merge into a single continuous sound. These echoes decrease in level with successive reflections, and eventually are completely absorbed by the room.

#### Non-Reverberant Environments

An open, outdoor space is considered to be a non-reverberant environment, as virtually all sound escapes the area without reflection.

#### Variations in Level Due to Distance for Non-Reverberant Environments

In non-reverberant environments, such as outdoors, sound pressure level will be reduced by half (6 dB) every time the distance from the speaker is doubled (this is called the inverse-square law). Figure A shows the dB losses to be expected as distance from the speaker is increased from the one-meter (3.28-foot) measuring distance typically used in SPL specifications.

#### Reverberant Environments

Where sound is reflected from walls and other surfaces, there is a point beyond which the "reverberant field" dominates and the sound pressure level is higher and more constant than predicted by using the inverse-square law alone.

#### Variations in Level Due to Distance for Reverberant Environments


The reverberant field will begin to dominate typically at distances of 10 to 30 feet. This distance is greatest for the least reverberant rooms and speakers with narrow beamwidth angles. The frequency and beamwidth specifications provided by the data sheet are still required to obtain satisfactory distribution of the direct sound (or direct field) from the loudspeaker(s), which still follows the inverse-square law. It is the direct signal that contributes to speech intelligibility. This is why the sound system designer should seek a uniform direct field, with as little reverberant field as possible. For example, consider a single speaker with a wide beamwidth angle used to cover a long, narrow, reverberant room. The direct field will be so far below the reverberant field at the back of the room that speech will probably be unintelligible.

#### Calculating Variations in Level Due to Changes in Electrical Power

Each time the power delivered to the speaker is reduced by one-half, a level drop of 3 dB occurs. The nomograph of Figure B shows the change in dB to be expected as the power varies from the one-watt input typically used in SPL specifications.

#### Power Handling

The power rating of a speaker must be known to determine whether a design is capable of meeting the sound pressure level requirements of the system. The power rating combined with the sensitivity will enable a system designer to calculate the maximum sound pressure level attainable at a given distance.



#### Powering to Achieve Both Average and Peak SPL

The average power that must be delivered to the speaker(s) to achieve the desired average SPL can be determined from the previously presented material on speaker sensitivity, level variation with distance and level variation with power. Enough additional power must be available to reproduce without distortion the short-term peaks that exist in voice and music program. This difference between the peak and average capability of a sound system, when expressed in dB, is often called "peak-to-average ratio," "crest factor" or "headroom." The peaks can be large, as noted earlier: at least 10 times the average (10 dB).

The better sound systems are designed for peaks that are 10 dB above the average, although 6 dB of headroom is sufficient for most general-purpose voice paging systems. The 10-dB peaks require amplifier power ten times that required for the average sound levels. The 6-dB peaks require four times the power.

#### Utilizing Speaker Beamwidth Information for Maximum Intelligibility

Knowing the beamwidth angle of a loudspeaker can aid in providing a uniform direct field in the listening area. After selecting a desired speaker location, the beamwidth angle needed to adequately cover the listeners without spilling over to the walls or ceilings must be determined. Once these angles are known, the correct speaker can be found by using catalog specifications.

#### Using Easy-VAMP™ and Floor-Plan Isobars

In some circumstances, it is desirable to use an approach that is more detailed than using the basic horizontal and vertical beamwidth angles. Environments which have excessive reverberation or high ambient noise levels make it especially difficult to achieve the desired SPL and intelligibility.

In recent years, a number of computer-based techniques have been developed to help sound system designers. Some of the more complex systems use personal computers, with relatively sophisticated graphics. Simpler systems, such as Electro-Voice's VAMP™ (Very Accurate Mapping Program), utilize clear overlays and require programmable scientific calculators. However, the hardware/software and training investment required to utilize even the simpler systems are not attractive to some sound systems designers. Because of this, University Sound has developed a special adaptation of VAMP, called Easy-VAMP™, which provides a similar design aid without the complexity and cost of the VAMP programs.

More information on both the Easy-VAMP™ and floor-plan isobars can be found in the University Sound Guide.

