

**SPECIFICATIONS**

|                                  |                         |
|----------------------------------|-------------------------|
| Impedance:                       | 8 ohms                  |
| Power Handling Capacity,         |                         |
| Program:                         | 30 watts                |
| Peak:                            | 60 watts                |
| EIA Sensitivity:                 | 57 dB                   |
| Magnet:                          | 1 pound Alnico V        |
| Free Air Resonance:              | 700 Hz                  |
| Recommended Crossover Frequency: | 800 Hz                  |
| Voice Coil Diameter:             | 2 inches                |
| Throat Diameter:                 | 7/8 inch                |
| Mounting:                        | 1-3/8"-18 thread        |
| Size:                            | 4-1/16" d x 3 3/4" dia. |
| Net Weight:                      | 4 lbs., 11 oz.          |
| Shipping Weight:                 | 6 lbs.                  |

**DESCRIPTION AND APPLICATIONS**

The T25A is a dynamic driver unit designed for primary use as a high fidelity, mid-range reproducer. An edge-wound aluminum voice coil drives a molded, phenolic impregnated cloth diaphragm for high efficiency with low distortion. The same engineering and production expertise developed for high-power commercial and military drivers is employed on the T25A, yielding an extremely rugged and dependable unit.

When used with a well-designed horn, such as the Electro-Voice Model 8HD, the T25A offers much improved performance throughout the middle of the audible spectrum. In addition to "filling in" the response curve where some large speakers tend to sag, the T25A greatly reduces distortion and improves transient response. The 8HD diffraction horn spreads the sound more uniformly over the listening area, thus improving stereo balance.

**MOUNTING**

The T25A may be secured by simply screwing the threaded mounting into the internally threaded throat of the 8HD horn. For home use, this mounting is sufficient to support the weight of the T25A driver. However, should this driver be used in a system which is handled roughly, such as a commercial sound loudspeaker system, then the weight of the T25A should be supported by strapping or otherwise securing the driver to the cabinet.

protection well in excess of shipping requirements of the Interstate Commerce Commission. If, however, shipping damage has occurred, contact the carrier or the dealer from whom the unit was purchased and request inspection and instructions.

**WARRANTY**

Electro-Voice high fidelity speakers, speaker systems, and accessories are guaranteed for five years from date of original purchase against malfunction due to defects in workmanship and materials. If such malfunction occurs, unit will be repaired or replaced (at our option) without charge for materials or labor if delivered prepaid to the proper Electro-Voice service facility. Unit will be returned prepaid. Warranty does not cover finish or appearance items or malfunction due to abuse or operation at other than specified conditions. Repair by other than Electro-Voice or its authorized service agencies will void this guarantee.

For correct shipping address and instructions on return of Electro-Voice products for repair and locations of authorized service agencies, please write: Service Department, Electro-Voice, Inc., 600 Cecil Street, Buchanan, Michigan 49107 (Phone: 616/695-6831).

Electro-Voice also maintains complete facilities for non-warranty service.