

Electro-Voice

DX-34 Programming Tables

Title:	DTS-640				
DX-34 Configuration:	3-Way Configuration				
Notes:					
AP Files:					
Programmer/Date:	Todd Jenkins 7/3/96				
	FR	#1	#2	#3	#4
Master Delay (ms):	2.0				
Master PEQ Freq (Hz):					
Master PEQ Q:					
Master PEQ Gain (dB):					
Low-Cut Freq (Hz):		50			
Low-Cut Slope (dB/Oct):		12			
Low-Cut Q:		2			
LSH Freq. (Hz):		136			
LSH Slope (dB/Oct):		12			
LSH Gain (dB):		0			
HP Freq. (Hz):			300	2400	
HP Filter Type:			L/R	Butter	
HP Slope (dB/Oct):			24	24	
PEQ1 Freq. (Hz):		100		4100	
PEQ1 Q:		1.7		1	
PEQ1 Gain (dB):		-2		-2	
PEQ2 Freq. (Hz):					
PEQ2 Q:					
PEQ2 Gain (dB):					
LP Freq. (Hz):		220	2400		
LP Filter Type:		L/R	Butter		
LP Slope (dB.Oct):		24	24		
HSH Freq. (Hz):				4700	
HSH Slope (dB/Oct):				6	
HSH Gain (dB):				7	
Delay (us):		0	0	0	
Polarity (Norm./Invert.):		Norm.	Norm.	Invert.	
Output Gain (dB):		5	0	-8	
Limiter Thresh. (dBU):		+21	+21	+21	
Limiter Decay (dB/ms):		50	50	50	
Limiter Hold (ms):		5	5	5	
Channel 1 Mode:		L			
Channel 4 Mode:					L+R