

Electro-Voice**DX-34 Programming Tables**

Title: DTS-640			
DX-34 Configuration: 2-Way Configuration			
Notes:			
AP Files:			
Programmer/Date: Todd Jenkins 7/3/96			
	FR	#1/#3	#2/#4
Master Delay (ms):	2.0		
Master PEQ Freq (Hz):			
Master PEQ Q:			
Master PEQ Gain (dB):			
Low-Cut Freq (Hz):		50	
Low-Cut Slope (dB/Oct):		12	
Low-Cut Q:		2	
LSH Freq. (Hz):		136	
LSH Slope (dB/Oct):		12	
LSH Gain (dB):		0	
HP Freq. (Hz):			300
HP Filter Type:			L/R
HP Slope (dB/Oct):			24
PEQ1 Freq. (Hz):		100	14400
PEQ1 Q:		1.7	1.7
PEQ1 Gain (dB):		-2	3
PEQ2 Freq. (Hz):			
PEQ2 Q:			
PEQ2 Gain (dB):			
LP Freq. (Hz):		220	
LP Filter Type:		L/R	
LP Slope (dB/Oct):		24	
HSH Freq. (Hz):			2600
HSH Slope (dB/Oct):			6
HSH Gain (dB):			0
Delay (us):		0	0
Polarity (Norm./Invert.):		Norm.	Norm.
Output Gain (dB):		5	0
Limiter Thresh. (dBu):		+21	+21
Limiter Decay (dB/ms):		50	50
Limiter Hold (ms):		5	5
Channel 1 Mode:		L	
Channel 4 Mode:			