

2-WAY MODE

DATE: 01-10-95

AUTHOR: David Gunness

SOFTWARE

TITLE: MH6040C

VERSION: 1.00

SPEAKER SYSTEM NAME: MH6040C

PARAMETER	INPUT	CH 1	CH 2	CH 3	CH 4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		1250 Hz			
MASTER PEQ Q		1.1			
MASTER PEQ GAIN		0 dB			
LO-CUT FREQ		76 Hz	76 Hz		
LO-CUT RESP		12 dB 2.0 Q	12 dB 2.0 Q		
LOSHLV FREQ			230 Hz		230 Hz
LOSHLV SLOPE			12 dB		12 dB
LOSHLV GAIN			+2 dB		+2 dB
HI-PASS FREQ			1250 Hz		1250 Hz
HI-PASS RESP			4th BW		4th BW
PEQ1 FREQ		720 Hz	7000 Hz	720 Hz	7000 Hz
PEQ1 Q		3.5	2.5	3.5	2.5
PEQ1 GAIN		+3 dB	+1 dB	+3 dB	+1 dB
PEQ2 FREQ			14000 Hz		14000 Hz
PEQ2 Q			1.6		1.6
PEQ2 GAIN			+10 dB		+10 dB
LO-PASS FREQ		1250 Hz		1250 Hz	
LO-PASS RESP		4th BW		4th BW	
HISHLV FREQ			4500 Hz		4500 Hz
HISHLV SLOPE			12 dB		12 dB
HISHLV GAIN			+6 dB		+6 dB
DELAY ALIGNM			0 us	3456 us	0 us
POLARITY		+	+	+	-
OUTPUT GAIN		+1 dB	-2 dB	+1 dB	-2 dB
LIMIT THRESH		21 dBu	21 dBu	21 dBu	21 dBu
LIMIT DECAY		50 dB/s	50 dB/s	50 dB/s	50 dB/s
LIMIT HOLD		0 ms	0 ms	0 ms	0 ms

100 Hz
12 dB 0.70 Q