

2-WAY MODE

DATE: 01-10-95

AUTHOR: David Gunness

SOFTWARE

TITLE: MH9040C

VERSION: 1.00

SPEAKER SYSTEM NAME: MH9040C

PARAMETER	INPUT	CH 1	CH 2	CH 3	CH 4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		1250 Hz			
MASTER PEQ Q		1.1			
MASTER PEQ GAIN		+5 dB			
LO-CUT FREQ		88 Hz	88 Hz		
LO-CUT RESP		12 dB 1.0 Q	12 dB 1.0 Q		
LOSHLV FREQ		230 Hz		230 Hz	
LOSHLV SLOPE		12 dB		12 dB	
LOSHLV GAIN		+12 dB		+12 dB	
HI-PASS FREQ		1360 Hz		1360 Hz	
HI-PASS RESP		4th BW		4th BW	
PEQ1 FREQ	720 Hz	7000 Hz	720 Hz	7000 Hz	
PEQ1 Q	3.5	2.5	3.5	2.5	
PEQ1 GAIN	+3 dB	+5 dB	+3 dB	+5 dB	
PEQ2 FREQ		14400 Hz		14400 Hz	
PEQ2 Q		4.0		4.0	
PEQ2 GAIN		+12 dB		+12 dB	
LO-PASS FREQ	1120 Hz		1120 Hz		
LO-PASS RESP	4th BW		4th BW		
HISHLV FREQ		4500 Hz		4500 Hz	
HISHLV SLOPE		12 dB		12 dB	
HISHLV GAIN		+6 dB		+6 dB	
DELAY ALIGNM	0 us	2837 us	0 us	2837 us	
POLARITY	+	+	+	+	
OUTPUT GAIN	-1 dB	-2 dB	-1 dB	-2 dB	
LIMIT THRESH	21 dBu	21 dBu	21 dBu	21 dBu	
LIMIT DECAY	50 dB/s	50 dB/s	50 dB/s	50 dB/s	
LIMIT HOLD	10 ms	0 ms	10 ms	0 ms	

100 Hz
12 dB 0.70 Q