

2-WAY MODE

Electro-Voice Dx-34 DSP Settings

DATE: April 16, 1996

AUTHOR: J.Morton

TITLE: MT-1 system 2-way settings (MTL-1 and MTH-1)

SPEAKER SYSTEM NAME: MT-1

SOFTWARE VERSION: 1.00

PARAMETER		CH 1	CH 2	CH 3	CH 4
MASTER DELAY	2 ms				
MASTER PEQ FREQ	Hz				
MATER PEQ Q					
MASTER PEQ GAIN	0 dB				
LO-CUT FREQ		40 Hz		Hz	
LO-CUT RESP		12 dB 1.5 Q		dB Q	
LOSHELV FREQ		Hz		Hz	
LOSHELV SLOPE		dB		dB	
LOSHELV GAIN		0 dB		dB	
HI-PASS FREQ			160 Hz		Hz
HI-PASS RESP			Link-Riley		
PEQ1 FREQ		Hz	6,000 Hz	Hz	Hz
PEQ1 Q			3.5		
PEQ1 GAIN		0 dB	-2 dB	dB	dB
PEQ2 FREQ			12,000 Hz		Hz
PEQ2 Q			1.4		
PEQ2 GAIN			+3 dB		dB
LO-PASS FREQ		160 Hz		Hz	
LO-PASS RESP		Link-Riley 24dB			
HISHELV FREQ			Hz		Hz
HISHELV SLOPE			dB		dB
HISHELV GAIN			0 dB		dB
DELAY ALIGNM		427 us	0 us	us	us
POLARITY		+	+		
OUTPUT GAIN		+4 dB	0 dB	dB	dB
LIMIT THRESH		21 dBu	21 dBu	dBu	dBu
LIMIT DECAY		50 dB/s	50 dB/s	dB/s	dB/s
LIMIT HOLD		5 ms	5 ms	ms	ms