

2-WAY MODE

DATE: 01-30-95

AUTHOR: Chris Stirling

SOFTWARE

TITLE: MTS-1

VERSION: V 1.00

SPEAKER SYSTEM NAME: MTS-1

PARAMETER	INPUT	CH 1	CH 2	CH3	CH4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		630 Hz			
MASTER PEQ Q		2			
MASTER PEQ GAIN		-6 dB			
LO-CUT FREQ		78 Hz		78 Hz	
LO-CUT RESP		12 dB 2.0 Q		12 dB 2.0 Q	
LOSHLV FREQ			108 Hz		108 Hz
LOSHLV SLOPE			12 dB		12 dB
LOSHLV GAIN			6 dB		6 dB
HI-PASS FREQ			760Hz		760Hz
HI-PASS RESP			4th BW		4th BW
PEQ1 FREQ		136 Hz	6300 Hz	136 Hz	6300 Hz
PEQ1 Q		3.1	2.5	3.1	2.5
PEQ1 GAIN		+7 dB	+5 dB	+7 dB	+5 dB
PEQ2 FREQ			1120 Hz		1120 Hz
PEQ2 Q			1.2		1.2
PEQ2 GAIN			+10 dB		+10 dB
LO-PASS FREQ		840 Hz		840 Hz	
LO-PASS RESP		4th BW		4th BW	
HISHLV FREQ			8600 Hz		8600 Hz
HISHLV SLOPE				12 dB	12 dB
HISHLV GAIN			+5 dB		+5 dB
DELAY ALIGNM			0 us	0 us	0 us
POLARITY		+	+	+	+
OUTPUT GAIN		0 dB	-3 dB	0 dB	-3 dB
LIMIT THRESH		21 dBu	21 dBu	21 dBu	21 dBu
LIMIT DECAY		50 dB/s	50 dB/s	50 dB/s	50 dB/s
LIMIT HOLD		10 ms	0 ms	10 ms	0 ms