

3-WAY MODE

DATE: 01-30-95

AUTHOR: David Gunness

SOFTWARE
VERSION: V 1.00

TITLE: PI64 + PI218L

SPEAKER SYSTEM NAME: PI64 + PI218L

PARAMETER	INPUT	CH 1	CH 2	CH 3	CH 4
MASTER DELAY 1-3		2.0 ms			
LO-CUT FREQ		40 Hz			
LO-CUT RESP		12 dB 1.5 Q			
LO-SHELV FREQ			172 Hz		
LO-SHELV SLOPE			12 dB		
LO-SHELV GAIN			+3 dB		
HI-PASS FREQ			136 Hz	1760 Hz	
HI-PASS RESP			4th LW	4th BW	
PEQ1 FREQ		66 Hz	740 Hz	8800 Hz	
PEQ1 Q		4.0	3.1	1.6	
PEQ1 GAIN		-2 dB	-2 dB	+10 dB	
PEQ2 FREQ			1400 Hz	14400 Hz	
PEQ2 Q			1.1	3.4	
PEQ2 GAIN			+6 dB	+11 dB	
LO-PASS FREQ		144 Hz	1360 Hz		
LO-PASS RESP		4th LW	4th BW		
HI-SHELV FREQ				3200 Hz	
HI-SHELV SLOPE					12 dB
HI-SHELV GAIN				-4 dB	
DELAY ALIGNM			299 us	0 us	1856 us 2 ms
POLARITY		+	+	+	+
OUTPUT GAIN		+2 dB	-4 dB	-8 dB	0 dB
LIMIT THRESH		21 dBu	21 dBu	21 dBu	
LIMIT DECAY		50 dB/s	50 dB/s	50 dB/s	
LIMIT HOLD		5 ms	5 ms	5 ms	
ILO &CH4 MODE					L/R