
3-WAY MODE

DATE: 01-30-95

AUTHOR: David Gunness

SOFTWARE

TITLE: PI94 + PI218L

VERSION: V 1.00

SPEAKER SYSTEM NAME: PI94 + PI218L

PARAMETER	INPUT	CH 1	CH 2	CH3	CH4
MASTER DELAY 1-3	2.0 ms				
LO-CUT FREQ	40 Hz				
LO-CUT RESP	12 dB 1.5 Q				
LO-SHELV FREQ		172 Hz			
LO-SHELV SLOPE		12 dB			
LO-SHELV GAIN		+3 dB			
HI-PASS FREQ		136 Hz	1960 Hz		
HI-PASS RESP		4th LW	4th BW		
PEQ1 FREQ	66 Hz	740 Hz	8800 Hz		
PEQ1 Q	4.0	3.1	1.6		
PEQ1 GAIN	-2 dB	-2 dB	+10 dB		
PEQ2 FREQ		1400 Hz	14400 Hz		
PEQ2 Q		1.1	3.4		
PEQ2 GAIN		+6 dB	+11 dB		
LO-PASS FREQ	144 Hz	1360 Hz			
LO-PASS RESP	4th LW	4th BW			
HISHELV FREQ			3200 Hz		
HISHELV SLOPE				12 dB	
HISHELV GAIN			-4 dB		
DELAY ALIGNM		299 us	0 us	1856 us	2 ms
POLARITY	+	+	+	+	
OUTPUT GAIN	+2 dB	-3 dB	-6 dB	0 dB	
LIMIT THRESH	21 dBu	21 dBu	21 dBu		
LIMIT DECAY	50 dB/s	50 dB/s	50 dB/s		
LIMIT HOLD	5 ms	5 ms	5 ms		
1LO & CH4 MODE					L/R