

2-WAY MODE

DATE: 08-02-95

AUTHOR: Matt Ruhlen

SOFTWARE

TITLE: PIM-122 (std confg.)

VERSION: V 1.00

SPEAKER SYSTEM NAME: PIM-122 (DL12x, HP94S w/DH2As2)

PARAMETER	INPUT	CH 1	CH 2	CH 3	CH 4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		1600 Hz			
MASTER PEQ Q		5			
MASTER PEQ GAIN		0 dB			
LO-CUT FREQ		42 Hz		42 Hz	
LO-CUT RESP		12 dB 0.7 Q			12 dB 0.7 Q
LOSHLV FREQ			120 Hz		120 Hz
LOSHLV SLOPE			12 dB		12 dB
LOSHLV GAIN			+7 dB		+7 dB
HI-PASS FREQ			1250 Hz		1250 Hz
HI-PASS RESP			Link 24		Link 24
PEQ1 FREQ		500 Hz	4100 Hz	500 Hz	4100 Hz
PEQ1 Q		1.0	1.0	1.0	1.0
PEQ1 GAIN		-7 dB	-4 dB	-7 dB	-4 dB
PEQ2 FREQ			2200 Hz		2200 Hz
PEQ2 Q			5.7		5.7
PEQ2 GAIN			-56 dB		-56 dB
LO-PASS FREQ		1250 Hz		1250 Hz	
LO-PASS RESP		Link 24		Link 24	
HISHLV FREQ			10000 Hz		10000 Hz
HISHLV SLOPE			12 dB		12 dB
HISHLV GAIN			+5 dB		+5 dB
DELAY ALIGNM			0 us	0 us	0 us
POLARITY		+	+	+	+
OUTPUT GAIN		-4 dB	-19 dB	-4 dB	-19 dB
LIMIT THRESH		21 dBu	21 dBu	21 dBu	21 dBu
LIMIT DECAY		50 dB/s	50 dB/s	0 dB/s	50 dB/s
LIMIT HOLD		5 ms	5 ms	5 ms	5 ms