

2-WAY MODE

DATE: 08-02-95

AUTHOR: Matt Ruhlen

SOFTWARE

TITLE: PIM-152 (std confg.)

VERSION: V 1.00

SPEAKER SYSTEM NAME: PIM-152 (DL15x, HP64S w/DH1A)

PARAMETER	INPUT	CH 1	CH 2	CH3	CH4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		1000 Hz			
MASTER PEQ Q		1			
MASTER PEQ GAIN		0 dB			
LO-CUT FREQ		32 Hz		32 Hz	
LO-CUT RESP		12 dB 0.7 Q			12 dB 0.7 Q
LOSHELV FREQ			192 Hz		192 Hz
LOSHELV SLOPE			12 dB		12 dB
LOSHELV GAIN			+7 dB		+7 dB
HI-PASS FREQ			1250 Hz		1250 Hz
HI-PASS RESP			Link 24		Link 24
PEQ1 FREQ		340 Hz	1600 Hz	340 Hz	1600 Hz
PEQ1 Q		1.0	5.0	1.0	5.0
PEQ1 GAIN		-5 dB	-7 dB	-5 dB	-7 dB
PEQ2 FREQ			4000 Hz		4000 Hz
PEQ2 Q			1.0		-6 dB
PEQ2 GAIN			-6 dB		
LO-PASS FREQ		1250 Hz		1250 Hz	
LO-PASS RESP		Link 24		Link 24	
HISHELV FREQ			8000 Hz		8000 Hz
HISHELV SLOPE				12 dB	12 dB
HISHELV GAIN			+6 dB		+6 dB
DELAY ALIGNM			704 us	0 us	704 us 0 us
POLARITY		+	+	+	+
OUTPUT GAIN		-1 dB	-11 dB	-1 dB	-11 dB
LIMIT THRESH		21 dBu	21 dBu	21 dBu	21 dBu
LIMIT DECAY		50 dB/s	50 dB/s	50 dB/s	50 dB/s
LIMIT HOLD		5 ms	5 ms	5 ms	5 ms