

2-WAY MODE

DATE: 08-02-95

AUTHOR: Matt Ruhlen

SOFTWARE

TITLE: PIM-252 (std confg.)

VERSION: V 1.00

SPEAKER SYSTEM NAME: PIM-252 (dual DL15x, HP64S w/DH1A)

PARAMETER	INPUT	CH 1	CH 2	CH 3	CH 4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		540 Hz			
MASTER PEQ Q		2.6			
MASTER PEQ GAIN		-2 dB			
LO-CUT FREQ		36 Hz		36 Hz	
LO-CUT RESP		12 dB 0.7 Q			12 dB 0.7 Q
LOSHLV FREQ			156 Hz		156 Hz
LOSHLV SLOPE			12 dB		12 dB
LOSHLV GAIN			+5 dB		+5 dB
HI-PASS FREQ			1250 Hz		1250 Hz
HI-PASS RESP			Link 24		Link 24
PEQ1 FREQ		270 Hz	3800 Hz	270 Hz	3800 Hz
PEQ1 Q		1.0	1.0	1.0	1.0
PEQ1 GAIN		-3 dB	-5 dB	-3 dB	-5 dB
PEQ2 FREQ			12800 Hz		12800 Hz
PEQ2 Q			8		8
PEQ2 GAIN			-3 dB		-3 dB
LO-PASS FREQ		1250 Hz		1250 Hz	
LO-PASS RESP		Link 24		Link 24	
HISHLV FREQ			7200 Hz		7200 Hz
HISHLV SLOPE				12 dB	12 dB
HISHLV GAIN			+5 dB		+5 dB
DELAY ALIGNM			704 us	0 us	704 us 0 us
POLARITY		+	+	+	+
OUTPUT GAIN		1 dB	-6 dB	1 dB	-6 dB
LIMIT THRESH		21 dBu	21 dBu	21 dBu	21 dBu
LIMIT DECAY		50 dB/s	50 dB/s	50 dB/s	50 dB/s
LIMIT HOLD		5 ms	5 ms	5 ms	5 ms