

2-WAY MODE

DATE: 1-30-95

AUTHOR: CHRIS STIRLING

SOFTWARE

TITLE: SH-1810

VERSION: 1.00

SPEAKER SYSTEM NAME: SH-1810

PARAMETER	INPUT	CH 1	CH 2	CH3	CH4
MASTER DELAY		2 ms			
MASTER PEQ FREQ		188 Hz			
MASTER PEQ Q		2.8			
MASTER PEQ GAIN		0 dB			
LO-CUT FREQ		40 Hz		40 Hz	
LO-CUT RESP		12 dB 1.5 Q		12 dB 1.5 Q	
LOSHELV FREQ			156 Hz		156 Hz
LOSHELV SLOPE			12 dB		12 dB
LOSHELV GAIN			+6 dB		+6 dB
HI-PASS FREQ			184Hz		184Hz
HI-PASS RESP			4th BW		4th BW
PEQ1 FREQ		200 Hz	210 Hz	200 Hz	210 Hz
PEQ1 Q		3.1	8.1	3.1	8.1
PEQ1 GAIN		+4 dB	+7 dB	+4 dB	+7 dB
PEQ2 FREQ			2700 Hz		2700 Hz
PEQ2 Q			2.9		2.9
PEQ2 GAIN			-4 dB		-4 dB
LO-PASS FREQ		180 Hz		180 Hz	
LO-PASS RESP		4th BW		4th BW	
HISHELV FREQ			7000 Hz		7000 Hz
HISHELV SLOPE				6 dB	6 dB
HISHELV GAIN			+1 dB		+1 dB
DELAY ALIGNM			0 us	0 us	0 us
POLARITY		+	+	+	+
OUTPUT GAIN		0 dB	-1 dB	0 dB	-1 dB
LIMIT THRESH		18 dBu	21 dBu	18 dBu	21 dBu
LIMIT DECAY		50 dB/s	50 dB/s	50 dB/s	50 dB/s
LIMIT HOLD		20 ms	0 ms	20 ms	0 ms