

2-WAY MODE

DATE: 9/2/97AUTHOR: K. LombardoTITLE: DL-34 SettingsSOFTWARE
VERSION: SPEAKER SYSTEM NAME: T-221M

PARAMETER		CH 1	CH 2	CH3	CH4
MASTER DELAY	<u>2</u> ms				
MASTER PEQ FREQ	<u>144</u> Hz				
MASTER PEQ Q	<u>2.2</u>				
MASTER PEQ GAIN	<u>3</u> dB				
LO-CUT FREQ		<u>56</u> Hz			
LO-CUT RESP		<u>6</u> dB Q			
LO-SHELV FREQ		<u>156</u> Hz			
LO-SHELV SLOPE		<u>12</u> dB			
LO-SHELV GAIN		<u>+9</u> dB			
HI-PASS FREQ			<u>1200</u> Hz		
HI-PAS RESP			<u>Link 24</u>		
PEQ1 FREQ		<u>820</u> Hz	<u>1040</u> Hz		
PEQ1 Q		<u>1.0</u>	<u>2.3</u>		
PEQ1 GAIN		<u>+4</u> dB	<u>-4</u> dB		
PEQ2 FREQ			<u>6400</u> Hz		
PEQ2 Q			<u>2.4</u>		
PEQ2 GAIN			<u>-4</u> dB		
LO-PASS FREQ		<u>1200</u> Hz			
LO-PASS RESP		<u>Link 24</u>			
HISHELV FREQ			<u>5800</u> Hz		
HISHELV SLOPE			<u>12</u> dB		
HISHELV GAIN			<u>+6</u> dB		
DELAY ALIGNM		<u>0</u> us	<u>0</u> us		
POLARITY		<u>N.I.</u>	<u>N.I.</u>		
OUTPUT GAIN		<u>0</u> dB	<u>-6</u> dB		
LIMIT THRESH		<u>21</u> dBu	<u>21</u> dBu		
LIMIT DECAY		<u>50</u> dB/s	<u>50</u> dB/s		
LIMIT HOLD		<u>5</u> ms	<u>5</u> ms		