

2-WAY MODE

Electro-Voice Dx-34 DSP Settings

DATE: 12-NOV-1996

AUTHOR: Kirk Lombardo

TITLE: T221 Two Way Crossover

SPEAKER SYSTEM NAME: T221

SOFTWARE VERSION:

PARAMETER		CH 1	CH 2	CH 3	CH 4
MASTER DELAY	2 ms				
MASTER PEQ FREQ	- Hz				
MATER PEQ Q	-				
MASTER PEQ GAIN	0 dB				
LO-CUT FREQ		66 Hz		Hz	
LO-CUT RESP		12 dB 0.8 Q		dB Q	
LOSHELV FREQ		210 Hz		Hz	
LOSHELV SLOPE		12 dB		dB	
LOSHELV GAIN		5 dB		dB	
HI-PASS FREQ			1200 Hz		Hz
HI-PASS RESP			Link 24		
PEQ1 FREQ		680 Hz	3800 Hz	Hz	Hz
PEQ1 Q		1.2	.9		
PEQ1 GAIN		-4 dB	-7 dB	dB	dB
PEQ2 FREQ			- Hz		Hz
PEQ2 Q			-		
PEQ2 GAIN			0 dB		dB
LO-PASS FREQ		1200 Hz		Hz	
LO-PASS RESP		Link 24			
HISHLV FREQ			7400 Hz		Hz
HISHLV SLOPE			6 dB		dB
HISHLV GAIN			+11 dB		dB
DELAY ALIGNM		555 us	0 us	us	us
POLARITY		N.I.	N.I.		
OUTPUT GAIN		+2 dB	-7 dB	dB	dB
LIMIT THRESH		21 dBu	21 dBu	dBu	dBu
LIMIT DECAY		50 dB/s	50 dB/s	dB/s	dB/s
LIMIT HOLD		5 ms	5 ms	ms	ms