

2-WAY MODE

Electro-Voice Dx-34 DSP Settings

DATE: 02/15/96

AUTHOR: J. Morton

TITLE: TS992-LX settings: uses the TL15-1XS and the HP99T/DH2As2 combination

SPEAKER SYSTEM NAME: TS992-LX

SOFTWARE VERSION: 1.00

PARAMETER		CH 1	CH 2	CH 3	CH 4
MASTER DELAY	2 ms				
MASTER PEQ FREQ	Hz				
MATER PEQ Q					
MASTER PEQ GAIN	0 dB				
LO-CUT FREQ		37 Hz		Hz	
LO-CUT RESP		12 dB 0.7 Q		dB Q	
LOSHLV FREQ		50 Hz		Hz	
LOSHLV SLOPE		12 dB		dB	
LOSHLV GAIN		+6 dB		dB	
HI-PASS FREQ			1,250 Hz		Hz
HI-PASS RESP			Link-Riley 24dB		
PEQ1 FREQ		760 Hz	2,500 Hz	Hz	Hz
PEQ1 Q		6.0	0.5		
PEQ1 GAIN		+5 dB	-9 dB	dB	dB
PEQ2 FREQ			7,400 Hz		Hz
PEQ2 Q			2.5		
PEQ2 GAIN			+4 dB		dB
LO-PASS FREQ		1,000 Hz		Hz	
LO-PASS RESP		Link-Riley 24dB			
HISHELV FREQ			10,000 Hz		Hz
HISHELV SLOPE			6 dB		dB
HISHELV GAIN			+6 dB		dB
DELAY ALIGNM		789 us	0 us	us	us
POLARITY		+	+		
OUTPUT GAIN		0 dB	-6 dB	dB	dB
LIMIT THRESH		21 dBu	21 dBu	dBu	dBu
LIMIT DECAY		50 dB/s	50 dB/s	dB/s	dB/s
LIMIT HOLD		5 ms	5 ms	ms	ms